



AS 2887
WMK 60121
AGA

NOTE:

- For general purpose use with acid, solvents and other aggressive chemicals.
- Injection moulded polypropylene (PP) in colours black, white & grey.
- To be installed in accordance with AS/NZS 3500.2.
- DN 50 loose nut union connection (fits standard 50mm trap).
- On installation, apply sealant under body flange. Sealant should be appropriate for the intended application.

REV.	DESCRIPTION	APP.	DATE



Viking Plastics Engineering Pty Ltd
143 Woodlands Drive, Braeside, VIC 3195, Australia
P: +613 9587 2297 | E: info@vikingplastics.com.au
www.vikingplastics.com.au

NAME	SIGNATURE	DATE	TITLE:
DRAWN PS		18-07-18	Plug & Washer Waste Outlet
CHK'D			
APPV'D			
MFG			
<small>This drawing is intended only for the use of the individual to whom it was forwarded by Viking Plastics Engineering Pty Ltd and contains information that is confidential and privileged. If you are not the intended recipient, you must not use, read, disclose, forward, copy or store any of the information. If you have received this drawing in error, please dispose of it and advise Viking Plastics +61 3 9587 2297.</small>			MATERIAL: PP/TPE DWG NO. P23 SCALE:1:1 SHEET 1 OF 1
WEIGHT:			A3 REV.